



THC2036HDB

Telecamera bullet HDCVI/AHD/TVI/CVBS, CMOS 1/2.7", 1.080p@25Fps, 3.6mm ICR, Starlight, 0.03Lux f2.0 ,IR30mt, WDR, 12Vdc<4,5W, IP67

Image Sensor	1/2.8" CMOS	
Effective Pixels	1937(H)×1097(V), 2.1MP	
Scanning System	Progressive	
Electronic Shutter	SpeedPAL: 1/4s~1/100000sNTSC: 1/3s~1/100000sMinimum	
Illumination	0.005Lux/F1.6, 30IRE, 0Lux IR on	
S/N Ratio	More than 65dB	
IR Distance	Up to 30m (98feet)	
IR On/Off	ControlAuto / ManualIR LEDs18	
Lens Type	Fixed lens / Fixed iris	
Mount Type	Board-in	
Focal Length	3.6mm (2.8mm, 6mm Optional)	
Max Aperture	F1.6Angle of ViewH: 87° (110.5°/52.9°)	
Focus Control	N/A	
Close Focus Distance	1200mm (500mm, 1800mm)47.24" (19.69", 70.87")	
DORI Distance		
Detect	25px/m (8px)	2.8mm: 42m / 3.6mm: 55m / 6mm: 81m
Observe	63px/m (19px)	2.8mm: 17m / 3.6mm: 22m / 6mm: 32m
Recognize	125px/m (38px)	2.8mm: 8m / 3.6mm: 11m / 6mm: 16m
Identify	250px/m (76px)	2.8mm: 4m / 3.6mm: 6m / 6mm: 8m
Pan/Tilt/Rotation	Pan: 0° ~ 360°Tilt: 0° ~ 90°Rotation: 0° ~ 360	
Video Resolution	1080P (1920×1080)	
Frame Rate	25/30fps@1080P, 25/30fps@720P	
Video Output	1-channel BNC high definition video output / CVBvideo output (Can switch)	
Day/Night	Auto (ICR) / Manual	
OSD Menu	Multi-languae	
BLC Mode	BLC / HLC / WDR	
WDR	120dB	
Gain Control	AGC	
Noise Reduction	2D / 3D	
White Balance	Auto / Manual	
Smart IR	Auto / Manual	
Power Supply	12V DC ±25%	
Power Consumption	Max 3.4W (12V DC, IR on)	
Operating Conditions	-40°C ~ +60°C	
IP Protection	IP67	
Dimensions	164.7mm×70mm×71.6mm	