



THC2030XIPSDIR

Speed dome IR IP 2Mp 25Fps EcoSavvy, CMOS 1/2.8", ICR,2-3DNR WDR, 30x+16x, 4.5~135mm, led 150mt, 2/1 IO allarmi, 24Vac<26W, IP66, (staffa THS305W non inclusa)

Sensore	1/2.8" STARVIS™ CMOS
Pixels effettivi	1920(H) x 1080(V), 2 Megapixels
Sistema di scansione	Progressivo
Velocità Shutter elettronico	1/1s~1/30,000s
Illuminazione minima	Color: 0.005Lux@F1.6; B/W: 0.0005Lux@F1.6; 0Lux@F1.6 (IR on)
Portata IR	oltre 200m
Numero di LEDs	6
Lunghezza focale	4.5mm~135mm
Angolo di visuale	H: 67.8° ~ 2.4°
DORI Distance	
Distance	1862m
Rilevazione	744m
Riconoscimento	372m
Identificazione	186m
Pan/Tilt Range	Pan: 0° ~ 360° endless; Tilt: -20° ~ 90°, auto flip 180°
Controllo velocità manuale	Pan: 0.1° ~200° /s; Tilt: 0.1° ~120° /s
Preset Speed	Pan: 300° /s; Tilt: 200° /s
PTZ Mode	5 Patern, 8 Tour, Auto Pan ,Auto Scan
Speed Setup	Human-oriented focal Length/ speed adaptation
Power up Action	Auto restore to previous PTZ and lens status afer power failure
Idle Motion	Actiate Preset/ Scan/ Tour/ Patern if there is no command in the specified period
Protocol	DH-SD, Pelco-P/D (Auto recognition
Intelligence Event Trigger	Motion detection, Video tampering , Scene changing, Network disconnection, IP address conflict, Illegal Access, Storage anomaly
Auto Tracking	Support
IVS	Tripwire, Intrusion, Abandoned/Missing
Advanced Intelligent Funct.	Face Detection, Het Map
Video Compression	H.265+/H.265/H.264+/H.264/MJPEG(Sub Stream)
Streaming Capability	3 Streams
Resolution	1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480)/CIF(352×288/352×240) Main stream: 1080P/1.3M/ 720P(1~50/60fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.265/H.264: 448K ~ 8192Kbps
Day/Night	Auto(ICR) / Color / B/W



Backlight Compensation	BLC / HLC / WDR (120dB)
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Gain Control	Auto / Manual
Noise Reductio	Ultra DNR (2D/3D)
Motion Detection	Support
Defog	Support
Digital Zoom	16x
Flip	180°
Privacy Masking	Up to 24 areas
Audio Compression	G.711a/G.711Mu/AAC/G.722 / G.726/G.729/MPEG2-L2
Ethernet	RJ-45 (10Base-T/100Base-TX)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
Interoperability	ONVIF Profile S&G, API
Streaming Method	Unicast / Multicast
Max. User Access	20 users
Edge Storage	NAS (Network Attached Storage), Local PC for instant recording, Micro SD card 256GB
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, DSS, DMSS
Smart Phone	IOS, Android
Video Interface	1 port(BNC, 1.0V[p-p], 75Ω)
RS485	1
Audio I/O	1/1
Alarm I/O	7/2
Power Supply	AC24V/3A(±25%), PoE+(802.3at)
Power Consumption	17W, 25W(IR On, Heater On)
Operating Condition	-40°C ~ 70°C
Ingress Protection	IP67
Vandal Resistance	IK10
Staffa THS305W	non inclusa
Dimensions (LxA)	209x337,4mm

